

“Ikarus” Hızlı Kum Filtreleri

TEKNİK ÖZELLİKLER



	Üstten Çok Yollu Vanalı				Yandan Çok Yollu Vanalı			
MODEL	300	400	450	500	300	400	450	500
D (mm)	300	400	450	500	300	400	450	500
H ₁ (mm)	735	815	865	940	590	670	720	800
H ₂ (mm)	500	580	630	705	500	580	630	705
H ₃ (mm)	-	-	-	-	530	610	660	740
H ₄ (mm)	-	-	-	-	215	240	225	300
H ₅ (mm)	-	-	-	-	355	385	395	440
W (mm)	-	-	-	-	260	260	260	260
BAĞLANTI (Ø)	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"
DEBİ (m ³ /h) (50 m ² /h/m ²)	3,54	6,30	8	10	3,54	6,30	8	10
KUM (Kg)	25	80	90	100	25	80	90	100
NET AĞIRLIK (Kg)	7,000	8,000	9,500	10,500	6,700	7,700	9,200	10,200

“Ikarus” Filtrasyon Üniteleri

TEKNİK ÖZELLİKLER



	Üstten Çok Yollu Vanalı				Yandan Çok Yollu Vanalı			
MODEL	300	400	450	500	300	400	450	500
D (mm)	680	685	685	855	680	685	685	870
H ₁ (mm)	770	875	945	990	625	725	770	845
H ₂ (mm)	535	640	710	755	535	640	710	755
H ₃ (mm)	-	-	-	-	565	665	710	785
H ₄ (mm)	-	-	-	-	-	-	-	-
H ₅ (mm)	-	-	-	-	-	-	-	-
W (mm)	-	-	-	-	-	-	-	-
W1 (mm)	565	565	565	575	625	675	720	760
BAĞLANTI (Ø)	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"
DEBİ (m ³ /h) (50 m ² /h/m ²)	3,54	6,30	8	10	3,54	6,30	8	10
KUM (Kg)	25	80	90	100	25	80	90	100
NET AĞIRLIK (Kg)	14,500	16,500	18,000	21,500	14,200	16,200	17,700	21,200

“Neptune” Filtrasyon Üniteleri

TEKNİK ÖZELLİKLER



	Üstten Çok Yollu Vanalı			Yandan Çok Yollu Vanalı		
MODEL	450	500	650	450	500	650
D (mm)	685	880	995	685	880	955
H ₁ (mm)	850	890	970	770	800	890
H ₂ (mm)	615	655	735	615	655	735
H ₃ (mm)	-	-	-	710	740	830
H ₄ (mm)	-	-	-	-	-	-
H ₅ (mm)	-	-	-	-	-	-
W (mm)	-	-	-	-	-	-
W1 (mm)	-	-	-	675	775	925
BAĞLANTI (Ø)	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"
DEBİ (m ³ /h) (50 m ² /h/m ²)	8	10	16	8	10	16
KUM (Kg)	80	100	150	80	100	150
NET AĞIRLIK (Kg)	34,050	36,950	39,850	33,850	36,650	39,550