

# Broadex®

## *Sand Filters For Swimming Pools*



Quality Management System



- Filter shell made of Laminated Fiberglass Reinforced Polyester.
- Large Transparent Lid of 40 cm diameter including the opening lever, pressure gauge, side mounted multiport valve and air purge.
- Test Pressure 3,5 kg/cm<sup>2</sup>.
- Max operation pressure 2,5 kg/cm<sup>2</sup>.
- Filtration Rate 50 m<sup>3</sup>/h/m<sup>2</sup>



### Lid detail

Lid inner diameter : 363 mm  
Lid outer diameter : 530 mm



## TECHNICAL CHARACTERISTICS

MODEL	BRO-LT 560 (021112LLT)	BRO-LT 615 (021113LLT)	BRO-LT 760 (021114LLT)	BRO-LT 830 (021115LLT)	BRO-LT 920 (021116LLT)	BRO-LT 1000 (021117LLT)	BRO-LT 1200 (021216LLT)
D (mm)	560	615	760	830	920	1000	1200
H <sub>1</sub> (mm)	800	820	960	1030	1110	1375	1280
H <sub>2</sub> (mm)	-	-	-	-	-	-	-
H <sub>3</sub> (mm)	740	760	900	970	1050	1325	1230
H <sub>4</sub> (mm)	285	260	350	360	375	515	455
H <sub>5</sub> (mm)	420	410	500	510	525	845	745
W (mm)	260	260	295	295	295	480	480
CONNECTIONS Ø (mm)	1 1/2"	1 1/2"	2"	2"	2"	2 1/2"	2 1/2"
FLOW (m <sup>3</sup> /h) (50 m <sup>3</sup> /h/m <sup>2</sup> )	12,5	15	22	27	32	39	56
SAND (Kg)	100	125	250	350	450	725	1330
NET WEIGHT (Kg)	20,000	25,000	32,000	40,000	50,000	70,000	77,000



Quality Management System

We reserve the right to change all or part of the features of the articles or contents of this document, without prior notice.

DISTRIBUTOR: