

Injectrone

Plastic Sand Filters for Swimming Pools



Quality Management System







- Made of injected PE.
- The upper and lower parts are combined with a special welding technique.
- As the bed depth is higher than other filter models, the filtration quality is considerably higher.
- Sand water discharge openings are available at both front and rear, installed w/discharge valve.
- Easy to open transparent screw lid (2 cm wider than bolted lid).
- Complete with multi-way valve, fittings, and pressure gauge.
- Five-year body warranty.
- Test pressure 3 kg/cm²
- Maximum operation pressure 2 kg/cm²
- Maximum filtration rate 50 m³/h/m²
- Burst pressure > 4 kg/cm²



Easy to open 23 cm transparent screw lid.




Monoblock filter connections integrated to filter body.



Sand water discharge openings are available at both front and rear, installed with discharge valve.

TECHNICAL CHARACTERISTICS

MODEL	0211011	0211012
D (mm)	500	600
H ₁ (mm)	960	1030
H ₂ (mm)	-	-
H ₃ (mm)	910	980
H ₄ (mm)	290	320
H ₅ (mm)	415	445
W (mm)	260	260
CONNECTIONS Ø (mm)	1 1/2"	1 1/2"
FLOW (m ³ /h) (50 m ³ /h/m ²)	9,81	14,13
SAND (Kg)	125	170
NET WEIGHT (Kg)	8,000	11,000



DISTRIBUTOR:



Quality Management System



We reserve the right to change all or part of the features of the articles or contents of this document, without prior notice.