POOL DIRECTOR®

Automatic water treatment for your pool





GEMAS Automatic Disinfection Systems ensure the continuity of optimal hygienic conditions and pH value by constantly controlling the pool water quality.

➤ When you are not at home even without moving a finger, clean, clear and ideal pool water:

DREAM OF POOL OWNERS!

- ▶ GEMAS, presents the latest technol ogy product for the provision and continuity of hygienic water quality in your pool!
- ➤ Pool Director® maintains optimal pH and Chlorine values in the pool water through continuous control.
- ► The function of **Pool Director**® is your gain.
- Automatic dosage of pool chemicals; Because it is much more sensitive, it is more economical than manual dosage.
- ▶ It guarantees an extremely safe water environment, as it automatically provides hygienic conditions that will destroy microbes that may enter the pool immediately.
- ▶ Due to the prevention of sudden changes in the chemical balance of the water, it saves from the correction processes.
- ➤ The ease of operation and time savings that the system will provide should not be forgotten.
- ► Pool Director® can also be installed in the existing pool systems very easily. It is extremely easy to maintain.



gemas.com.tr

Technical Features

Measurement and Adjustment Unit:

Voltage : 220 V / 50 Hz

Insulation Class : IP 54

Electrode Connection: BNC Socket

Disinfection:

Chlorine Measurement: Metal Single Rod Electrode

Measurement Range : 0 - 1500 mV

Accuracy : ± %1

Indicator : 4x20 LCD screen

Calibration Liquid : Redox 475 mV buffer solution

Adjustment Unit : Proportional Relay : 8 A / 220 V AC

Dosage Label : Red LED

Operating Modes : Manual dosing - Measuring -

Automatic measurement and dosing

pH - Value:

pH - Measurement : Metal Single Rod Electrode

Measurement Range : pH 0 to pH 14

Accuracy : \pm %1

Indicator : 4x20 LCD screen

Calibration Liquid : pH 4 and pH 7 buffer solution

Adjustment Unit : Proportional Relay : 8 A / 220 V AC

Dosage Label : Red LED

Operating Modes : Manual dosing - Measuring -

Automatic measurement and dosing

Package Content

The unit mounted on a plastic panel with dimensions of 78x56x19 consists of the following elements;

1 Measurement and Adjustment Unit **Pool Director**®

2 Unit Dosage Pumps (Optional)

1 Unit pH Electrode. With 1,5 m cable and BNC socket 1 Unit Redox Electrode. With 1,5 m cable and BNC socket